

E10z


Excavators

Specifications

Weights	
Operating weight with TOPS canopy and bucket (ISO 6016)	1176 kg
Transport mass (no attachment)	1077 kg
Ground pressure with rubber tracks	29.70 kPa
Engine	
Make / model Fuel	Kubota / D722-E4B (Stage V) Diesel
Number of cylinders	3
Displacement	719 cm ³
Maximum power @ 2000 rpm (ISO 14396)	7.5 kW
Maximum torque (SAE)	40.1 Nm
Hydraulic System	
Pump type	Double gear pump
Total hydraulic capacity	20.00 L/min
Auxiliary flow	20.00 L/min
Auxiliary relief	190.0 bar
Performance	
Digging force, dipperstick (ISO 6015)	5550 N
Digging force, bucket (ISO 6015)	8294 N
Drawbar pull	9905 N
Travel speed, low range Travel speed, high range	2.1 km/h 3.1 km/h
	3.1 KIII/II
Slew System	
Boom swing, left	67.0°
Boom swing, right	64.0°
Slew rate	9.0 RPM
Fluid Capacities	
Fuel reservoir	16.00 L
Hydraulic reservoir	2.60 L
Environmental	
Noise level LpA(EU Directive 2006/42/EC)	80 dB(A)
Noise level LWA(EU Directive 2000/14/EC)	93 dB(A)
Standard Features	
710 mm dozer blade / 1100 mm extended	Seat
180 mm rubber track	Two-speed travel
Auxiliary hydraulics on boom with quick couplers	TOPS canopy 1
Control console locks Horn	Vandalism protection Water separator
Electronically activated track expansion	Work light
Hydraulically expandible undercarriage from 710 to 1100	Warranty: 24 months, 2000 hours (whichever occurs first)
mm	Transaction of the state of the
Retractable seat belt	
1 Tip Over Protective Structure (TOPS) Meets requirements of ISO 12117	


1. Tip Over Protective Structure (TOPS) - Meets requirements of ISO 12117


Working Range



(A)	196.0°	(G)	1899.0 mm
(B)	3145.0 mm	(H)	2685.0 mm
(C)	3093.0 mm	(I)	1818.0 mm
(D)	1374.0 mm	(J)	1383.0 mm
(E)	196.0 mm	(K)	1820.0 mm
(F)	230.0 mm		

Dimensions





(A)	220.0 mm	(J)	710.0 mm
(B)	363.0 mm	(J)	1100.0 mm
(C)	992.0 mm	(K)	2209.0 mm
(D)	968.0 mm	(L)	180.0 mm
(E)	987.0 mm	(M)	413.0 mm
(F)	2153.0 mm	(N)	471.0 mm
(G)	1280.0 mm	(O)	1121.0 mm
(H)	2793.0 mm	(P)	550.0 mm
(I)	16.0 mm	(S)	1490.0 mm

Options

Auxiliary double action Auxiliary on arm Beacon Demolition package (arm, bucket cylinder covers & HD travel hoses guard) Grease Gun w/ holder Hydraulic oil cooler Keyless ignition LED light Object handling device (lifteye) Spark arrester muffler kit

Travel motion alarm