

Performance

Tipping load (ISO 14397-1)	2049 kg
Rated operating capacity (no more than 35% of Tipping Load)	717 kg
Pump capacity	63.00 L/min
System relief at quick couplers	22.4-23.1 MPa
Max. travel speed	10.0 km/h
Max. travel speed (high range – optional)	14.4 km/h

Engine

Make / Model	Bobcat 2.4L, 97/68 EC Stage V
Fuel	Diesel
Cooling	Liquid
Power at 2600 RPM (ISO 14396)	41.0 kW
Torque at 1800 RPM (ISO 14396)	204.2 Nm
Number of cylinders	4
Displacement	2393 cm ³
Fuel tank	64.90 L

Weights

Operating weight	2961 kg
Shipping weight	2665 kg
Ground pressure	34.00 kPa

Controls

Vehicle steering	Direction and speed controlled by two hand levers or optional joysticks
Loader hydraulics tilt and lift	Separate foot pedals or Selectable Joystick Control (SJC)
Front auxiliary (standard)	Electrical switch on right-hand steering lever

Drive System

Transmission	Infinitely variable tandem hydrostatic piston pumps, driving two fully reversing hydrostatic motors
--------------	---

Standard Features

Bobcat Interlock Control System (BICS)	Cushioned lift and tilt cylinders
Parking brake	Lift arm support
Deluxe operator cab* Includes interior cab foam, side, top and rear windows, Deluxe wire harness, dome light and electrical power port ¹	Engine/hydraulics system shutdown
Noise reduction kit	Spark Arrester
Operating lights, front and rear	Automatically activated glow plugs
Deluxe instrument panel	Electrically activated proportional front auxiliary hydraulics
Keyless start with password capability	Auxiliary hydraulics: variable flow/maximum flow
Suspension seat	Machine IQ (telematic)
Seat belt	Manual
Seat bar	CE certification
Tracks — rubber — 300 mm	Warranty: 24 months or 2000 hours (whichever occurs first)
Bob-Tach™ frame	


¹ Roll Over Protective Structure (ROPS) – meets requirements of SAE-J1040 and ISO 3471; Falling Object Protective Structure (FOPS) - meets requirements of SAE-J1043 and ISO 3449, Level I

Options

Deluxe pressurized cab with heating	Radio
Deluxe pressurized cab with HVAC	Strobe
Selectable Joystick Controls (SJC)	Back-up alarm
2 Speed	Beacon
Cloth Suspension Seat	Work Lights LED
Attachment control device	Road Option
Hydraulic bucket positioning (including ON/OFF switch)	Custom paint color (min order of 5 units)
Power Bob-Tach™	

Environmental

Operator LpA (98/37 & 474-1)	85 dB(A)
Noise level LWA (EU Directive 2000/14/EC)	101 dB(A)
Whole body vibration (ISO 2631-1)	1.00 ms ⁻²
Hand-arm vibration (ISO 5349-1)	2.42 ms ⁻²

Dimensions


(A)	3604.0 mm	(J)	2781.0 mm
(B)	1976.0 mm	(K)	597.0 mm
(C)	28.0°	(L)	40.0°
(D)	213.0 mm	(M)	91.0°
(E)	1275.0 mm	(N)	1422.0 mm
(F)	2499.0 mm	(N*)	1575.0 mm
(G)	3216.0 mm	(O)	1979.0 mm
(H)	26.0°	(P)	1097.0 mm
(I)	2129.0 mm	(Q)	1397.0 mm

Attachments

Auger Accessories	Pallet Fork Accessories
Augers	Pallet Forks, Hydraulic
Backhoes	Planer Accessories
Bale Forks	Rear Stabilizers
Box Blades	Remote Control
Breaker Accessories	Root Grapples
Breakers	Scarifiers
Brushcat™ Rotary Cutters	Scrapers
Brush Saws	Seeders
Combination Buckets	Skeleton Buckets
Concrete Mixers	Snow Blades
Construction / Industrial Buckets	Snow Pushers
Diggers	Snow V-Blades
Dozer Blades	Sod Layers
Dumping Hoppers	Soil Conditioners
Flail Cutters	Spreader
Graders	Sweepers
Grapples, Industrial	Tillers
Landplanes	Tilt-Tatch
Landscape Rakes	Utility Forks
Laser Equipment	Utility Frames
Low Profile Buckets	Vibratory Rollers
Miscellaneous	Wood Chippers
Mowers	